


# TECHNICAL SPECIFICATION: DUNBAR Liquid Mud Delivery Hose



## Construction

- Tube:** Black nitrile rubber
- Reinforcement:** Synthetic cord plies and copper wire
- Cover:** Black PVC/NBR rubber with 2 red stripes
- Temperature Range:** -25°C to +70°C

## Typical Application:

Fuel Oil, Liquid Mud containing Crude Oil and Grit delivery in offshore applications  
Maximum aromatic content: 30%

Part Number	Inside Diameter		Outside Diameter		Working Pressure		Min. Burst Pressure		Min. Bend Radius	Weight	Cont. Length
	mm	inch	mm	inch	BAR	PSI	BAR	PSI	mm	Kg/m	Mtr
Offshore Dunbar 55	102	4	137	5.4	55	825	164*	2460	650	7.39	120

\*Working pressure is 45 bar with DNV certification

End fittings and safety accessories available include but are not limited to: API Male Threads, Hammer Unions, Flanges, Camlocks, Victualic Grooved Inserts, Dry Break Couplings, Weaklink/Breakaways, Lifting Hooks c/w safety clamps, lace up and clip on reflective flotation collars.



## DET NORSKE VERITAS

TYPE APPROVAL CERTIFICATE

CERTIFICATE NO - TAP00000BJ